

A Cooper Lighting Solutions business


LIGHTING THAT IMPROVES WORKSITE SAFETY



JR Series

2,000 – 5,000 lumen fixture

120-277 VAC | 347 VAC*
2.58 kg | 5.68 lbs
7.0" x 8.0" x 4.4"
-40°C to +60°C
IP66/IP67/IP68*



GS Series

582 – 5,125 lumen fixture

4 Lengths
120 VAC | 12 VDC | 24 VDC
-40°C to +65°C
IP66 / IP67 / IP68*



LS Series

1,550 lumens per module

120 VAC
1.2 kg | 2.6 lbs per module
9.7" x 3.3" per module
-50°C to +70°C
IP66 / IP67



MR Series

3,000 – 6,000 lumen fixture

120-277 VAC | 347 VAC
4.6 kg | 10.4 lbs
14.5" x 11.5" x 2.5"
-40°C to +55°C
IP66 / IP67 / IP68*



BL Series

2,540 – 4,475 lumen fixture

120-277 VAC | 347 VAC*
2.90 kg | 6.4 lbs
18.43" x 5.65" x 3.93"
-50°C to +65°C
IP66 / IP68*



CANLED Series

469 – 587 lumen fixture

12-24 VDC
1.04 kg | 2.3 lbs
Ø3.47" x 5.29"
-40°C to +55°C
IP66



XR Series

8,000 – 20,000 lumen fixture

120-277 VAC | 347-480 VAC
8.1 kg | 17.8 lbs
18.74" x 14.88" x 3.78"
-50°C to +75°C
IP66 / IP68*



NL Series

3,970 – 14,313 lumen fixture

2 Lengths
120-277 VAC | 347-480 VAC
-40°C to +55°C
IP66



XCANLED Series

1,996 – 2,334 lumen fixture

12-24 VDC
4.3 kg | 9.5 lbs
Ø7.0" x 5.0"
-40°C to +55°C
IP66



AR Series

10,000 – 48,000 lumen fixture

120-277 VAC | 347-480 VAC
16.4 kg | 36.0 lbs
24.0" x 20.0" x 4.3"
-40°C to +55°C
IP66 / IP67



EXC Series

1,220 lumen fixture

120-277 VAC | 22-28 VDC
4.4 kg | 9.8 lbs
11.5" x 6.5" x 3.76"
-40°C to +55°C
IP66



ZLM Series

22,000 – 28,000 lumen fixture*

120-277 VAC
10.0 kg | 22.0 lbs
15.5" x 6.8" x 7.1"
-40°C to +45°C
IP66



See All Products



Listed weights are fixtures only (excluding mounts)

Further certification details on the next page

*Rated for General Location use only

